

Remote Programmable Power Supplies with Digital Displays

- Remote Sensing for precise regulation
- Remote analog programming for both Constant Voltage and Constant Current modes
- Output load may be turned on or off by remote control
- Series & Parallel Master/Slave and Tracking operation
- Excellent Load, Line Regulation and Ripple Specs
- LED display for both current and voltage
- All inputs and outputs are isolated
- Fine and Coarse controls

**3060R****6030R**

SPECIFICATIONS ■

[3060R]

Output Characteristics

Output Volts: 0 to $\pm 30V$; Output Amps: 0 to $\pm 6A$

Constant Voltage Mode

Load Regulation: 5mV; Line Regulation: 5mV

Noise and Ripple: 0.5mV RMS

Constant Current Mode

Load Regulation: 15mA; Line Regulation: 6mA

Noise and Ripple: 3mA RMS

Digital Display

Resolution Volts: 100mV; Amps: 100mA

Accuracy Volts: $\pm(0.2\% + 2d)$; Amps: $\pm(1.0\% + 3d)$

General Specifications

AC Input Volts: 100/230V selectable

Power Consumption: 450VA

Operating Temp: 0 to 40°C (32 to 104°F)

Size: 8.0" H x 8.3" W x 12.8" D

Weight: 22 lbs

Supplied Accessories: Manual, Power cord, Leads

[6030R]

Output Characteristics

Output Volts: 0 to $\pm 60V$; Output Amps: 0 to $\pm 3A$

Constant Voltage Mode

Load Regulation: 8mV; Line Regulation: 8mV

Noise and Ripple: 1mV RMS

Constant Current Mode

Load Regulation: 15mA; Line Regulation: 3mA

Noise and Ripple: 2mA RMS

Digital Display

Resolution Volts: 100mV; Amps: 100mA

Accuracy Volts: $\pm(0.2\% + 2d)$; Amps: $\pm(1.0\% + 3d)$

General Specifications

AC Input Volts: 100/230V selectable

Power Consumption: 380VA

Operating Temp: 0 to 40°C (32 to 104°F)

Size: 8.0" H x 8.3" W x 12.8" D

Weight: 22 lbs

Supplied Accessories: Manual, Power cord, Leads