

4 - 1/2 Digit Bench Top Digital Multimeter True RMS with RS232

B4004



B4004

- AC line or Battery operated
- 0.05% DC V Accuracy
- Measures Frequency to 220MHz
- MIN/MAX, Peak MIN/MAX and Relative modes
- Capacitance, and Temperature measurements
- Back lit display, Auto power off and Auto/Manual ranging
- True RMS AC Volts and Amps measurements
- Optically isolated RS232 interface
- PC Link software and RS232 to USB cable included
- CATII 1000V & CATIII 600V
- Can be used with clamp current transducers Protek 601C or 602C for high current measurements

SPECIFICATIONS

■ DC Voltage

Ranges: 200mV, 2V, 20V, 200V and 1000V
 Best Resolution: 10µV
 Accuracy: $\pm(0.05\% + 6d)$
 Input Impedance: 10MΩ
 Overload Volts: 1000V DC or 750V AC RMS

■ AC Voltage

Ranges: 200mV, 2V, 20V, 200V and 750V
 Best Resolution: 10µV
 Accuracy: $\pm(0.5\% + 30d)$ 40Hz to 60Hz
 $\pm(1.0\% + 30d)$ 60Hz to 5KHz
 $\pm(2.0\% + 30d)$ 5KHz to 10KHz
 Input Impedance: 10MΩ
 Overload Volts: 1000V DC or 750V AC RMS

■ DC Current

Ranges: 200µA, 2000µA, 20µA, 200mA, 10A
 Best Resolution: 10nA
 Accuracy: $\pm(0.15\% + 15d)$
 Overload Protection: 0.3A/250V and 10A/250V fuse

■ AC Current

Ranges: 200µA, 2000µA, 20mA, 200mA, 10A
 Best Resolution: 10nA
 Accuracy: $\pm(1.0\% + 30d)$ 60Hz to 1KHz:
 $\pm(1.2\% + 30d)$ 1KHz to 5KHz:
 Overload protection: 0.3A/250V and 10A/250V fuse

■ Resistance

Ranges: 200Ω, 2KΩ, 20KΩ, 200KΩ, 2MΩ, 20MΩ
 and 200MΩ
 Best Resolution: 10mΩ
 Accuracy: $\pm(0.1\% + 10d)$ 200Ω to 2MΩ ranges
 $\pm(0.5\% + 10d)$ 20MΩ range
 $\pm(2.0\% + 10d)$ 200MΩ range

■ Logic Frequency

Ranges: 20Hz to 220MHz
 Best Resolution: 1mHz
 Accuracy: $\pm(0.06\% + 10d)$
 Overload Protection: 250V

■ Linear Frequency

Input Range	Sensitivity(True RMS)	
	5Hz to 10KHz	10KHz to 100KHz
200mV	5mV	10mV
2V	50mV	100mV
20V	500mV	10V
200V	5V	10V

■ Temperature

Ranges: -30° C to 1300 °C (-22°F to 2372°F)
 Accuracy: $\pm(1\% + 2d)$

■ Duty Cycle

Ranges: 5% to 95%
 Accuracy: $\pm 10\%$

■ Capacitance

Ranges: 20nF, 200nF, 2µF, 20µF, 200µF, 2000µF,
 20mF, 200mF
 Best Resolution: 10 pF
 Accuracy: $\pm(1.2\% + 30d)$ 20nF to 20µF ranges
 $\pm(2.2\% + 30d)$ 200µF to 20mF ranges
 200mF unspecified
 Overload Protection: 250V

■ Diode test

Test Volt: 3V
 Test Current: 0.6mA
 Overload Protection: 250V

■ Continuity

Buzzer will sound @ <30Ω Resistance
 Overload Protection: 250V

■ Safety: IEC61010-1 CATII 1000V and CATIII 600V

■ General Specifications

Size: 9"(L) x 9.4"(W) x 3.3"(D)
 Weight: 3.3 lbs
 Power: 9V NEDA battery or 120V AC @ 60Hz
 Accessories: Test leads, Operating manual, RS-232
 cable to USB cable and PC Link software
 Temp adapter & thermocouple